



DX3224S

Multi-Channel Encoder



Product Overview

DEXIN DX3224S multi-channel encoder is our newest professional HD video encoding and multiplexing device with powerful functionality. It is equipped with 4/8/12 HDMI channels input supporting MPEG-4 AVC/H.264 video encoding and MPEG1 Layer II audio encoding. It can multiplex the 4/8/12 encoded TS to generate MPTS output through DATA port. It adopts the slot structure with one device supporting maximum 3 DX224S modules. Each module can work standalone. In conclusion, its high integration and cost-effective design make this device widely used in variety of digital distribution systems such as CATV digital head-end, terrestrial digital TV, etc.

Key features

- **4/8/12×HDMI video inputs with MPEG-4 AVC/H.264 Video encoding**
- **Support MPEG1 Layer II, support audio gain adjustment**




All the specifications are subject to change without any further notice. All rights reserved.

Add: No. 10 & No. 12, Wuxing Fourth Road, Wuhou District, Chengdu 610045, Sichuan, P.R. China
www.dsdtv.com/English Tel: +86-028-85558928 Fax: +86-028-85585255 Email: sunyu@dsdtv.com

- Support IP (MPTS) output over UDP and RTP protocol
- Support Null PKT Filter
- **Support Logo, Caption, QR Code insertion**(Language Supported: 中文, English, العربية, ไทย, हिन्दी, русская, اردو , for more languages please consult us...)
- Real-time effective encoding output bit-rate monitoring
- Control via web management, and easy updates via web
- Modular design,1U chassis support up to 3 modules
- **Lowest cost per channel, breakthrough price**

Principle Chart (per daughter module)



Technical specification

Input	4/8/12 HDMI inputs		
Video	Resolution	Input	1920×1080_60P,1920×1080_60i,1920×1080_50P,1920×1080_50i,1280×720_60P,1280×720_50P,720×576_50i,720×480_60i
		Output	1920×1080_30P,1920×1080_25P,1280×720_30P,1280×720_25P,720×576_25P,720×480_30P
	Encoding	MPEG-4 AVC/H.264	
	Bit-rate	1~13Mbps each channel	
	Rate Control	CBR/VBR	
	GOP Structure	IP...P (P Frame adjustment, without B Frame)	
Audio	Encoding	MPEG1 Layer II	
	Sampling rate	48KHz	
	Resolution	24-bit	
	Audio Gain	0-255 adjustable	
	Bit-rate	64/128/192/224/256/320/384Kbps (each channel)	
Stream output	IP (MPTS) output over UDP and RTP, 1000 Base-T Ethernet interface (Multicast/Unicast)		
System function	Network management (WEB)		
	Chinese and English language		
	Ethernet software upgrade		

Miscellaneous	Dimension(W×L×H)	482mm×328mm×44mm
	Environment	0~45℃(work); -20~80℃ (Storage)
	Power requirements	AC 110V± 10%, 50/60Hz, AC 220 ± 10%, 50/60Hz

Order Information

	Version I	VersionII	VersionIII
4 HDMI Input	○		
8 HDMI Input		○	
12 HDMI Input			○