




NDS3344C

IP QAM Modulator



Outline

NDS3344C IP QAM modulator is an all-in-one device integrated with multiplexing, scrambling and modulation in one case. It has 512 IP (SPTS/MPTS) input over UDP/RTP with 4 Ethernet ports. After multiplexing, scrambling and modulating process, it gives 4 DVB-C adjacent carriers (30MHz~1000MHz) output through the RF output interface. To meet customers' various requirements, this device is also equipped with 1 data port for 4 IP (SPTS/MPTS) output over UDP protocol.

With the features of low cost and high performance, NDS3344C is very adaptable to IPTV system.

Key Features

- **4 Ethernet IP input port (IPTV 1,2,3,4)**
- **512 IP (SPTS/MPTS) input over UDP/RTP protocol**
- **Support up to 748 PIDS remapping per channel**
- **Support accurate PCR adjusting/PSI/SI editing and inserting /PID Remapping/PID pass**
- **Excellent RF output performance index, MER \geq 40db**
- **4 multiplexed or scrambled TS over UDP output**
- **4 adjacent QAM carriers output, compliant to DVB-C (EN 300 429) and ITU-T J.83 A/B/C**



All the specifications are subject to change without any further notice. All rights reserved.

Address: No. 10 & No. 12, Wuxing Fourth Road, Wuhou District, Chengdu 610045, Sichuan, P.R. China
www.dsdvb.com/English Tel: +86-028-85558928 Fax: +86-028-85585255 Email: sunyu@dsdvb.com

- USB for upgrading CPU/FPGA
- Support IPTV Sync and NTP function
- Support Web-based Network management

Specifications

Input	512 IP (SPTS/MPTS) input over UDP/RTP protocol, 4*100M Ethernet ports			
Multiplexing	Maximum PID Remapping	748 per input channel		
	Function	PID remapping (automatically or manually)		
		Accurate PCR adjusting		
		Generate PSI/SI table automatically		
Scrambling	Maximum simulcrypt CA	4		
	Standard	ETSI 101 197, ETSI 103 197		
	Connection	Local/remote connection		
Modulation	QAM Channel	1 F typed output port for 4 carriers, 75Ω		
	Standard	EN300 429/ITU-T J.83A/B/C		
	MER	≥40db		
	RF Frequency	30~1000 MHz, 1kHz stepping		
	RF Output level	-10dBm~+0dBm, 0.1dB stepping		
	FEC	RS (204, 188)		
	Symbol Rate	5.0Msps~9.0Msps, 1ksps stepping		
		J.83A	J.83B	J.83C
	Constellation	16/32/64/128/256QAM	64/256 QAM	64/256 QAM
	Bandwidth	8M	6M	6M
Stream Out	4 IP (SPTS/MPTS) output over UDP, 1*1000M Ethernet port (IPTV Port)			
System	Web-based Network management			
	Chinese and English Language			
	Web and USB software upgrade			
General	Dimension	430mm×180mm×44mm (W*L*H)		
	Temperature	0~45°C (Operation) ; -20~80°C (Storage)		
	Power	AC 100V±10%/50/60Hz; AC 220V±10%, 50/60HZ		

Working Principle

